



# HEADY



## APPLICATION

1 or 2 actuators for swing gates

## CONTROL UNIT POWER SUPPLY

230 Vac - 50/60 Hz

## MOTORS POWER SUPPLY

230 Vac / 500 W + 500 W

## MAIN FUNCTIONS

Integrated LCD display | Integrated 433.92 MHz 64-code radio receiver with 3 encoding systems (Advanced Rolling Code, Rolling Code, Fixed Code) | Removable terminal boards | Automatic, and semi-automatic logic | Step by step, pedestrian and stop inputs | Separate photocell inputs in opening-closing and in closing phases | Output for electric lock 230 VAC/service light | Output for connecting flashing light | Output as gate open indicator, second radio channel and photocell testing | Separate electronic torque adjustment for each motor and operating times | Fixed slow-downs | Advantouch system to configure parameters and manage radio transmitters | Number of maneuvers | Programming access password | Maintenance warning



### E.LOCK

230 Vac vertical electric lock, supplied with counterplate.



### E.LOCKSE

Extended cylinder for E.LOCK electric lock. It allows unlocking gates up to 55mm-thick from the outside.

**AUTOMATISMI BENINCA SpA** • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com

